

# CFT Carhauler Series

## (Steel Floor-Tilt)

Specifications	
• G.V.W.R. - 12,000#	• Axle - (2) 6,000# Cambered Electric Brake
• G.A.W.R. (Each Axle) - 6,000#	• Suspension - Multi-Leaf Spring w/ Equalizer
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST235/80R16 Load Range E
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)
• Jack - Bolt-On 7K Top Wind Drog Leg	• Deck - 11 Ga. Diamond Plate
• Tongue - 2x6" Tube	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 2x6" Tube	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x72" - Removeable Diamond Plate	• Paint - Super Durable Powdercoat
• Loading - Straight Approach Plate w/ Recessed Lights & Chain Slot Tie Downs	

Optional Features	
• Front Wind Dam	• Maxx Chain Slot Package
• Gooseneck Model	• Battery Charger/Jack Options
• Winch Mount/Wire Kit	• Spare Mount & Wheel Options

Dimensions					
Weight/Length	A	B	C	D	E
3,700# - 20'	240"	129"	57"	20"	83"
3,900# - 22'	264"	140"	57"	20"	83"

