

10/12T (Commercial) Tilt Series

Fabricated-Deck

Specifications	
• G.V.W.R. - 23,900#	• Axle - (2) 10,000# Oil-Bath Electric Brake
• G.A.W.R. (Each Axle) - 10,000#	• Suspension - 3" HD-Leaf Spring w/ Equalizer
• Coupler - 2-5/16" - Adjustable (Gooseneck/Pintle)	• Tires - ST235/80R16 Load Range E
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - Dually 16" 8-Bolt Grey (8 on 6.5 Pattern)
• Jack - Bolt-On 10K Side Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Frame- 12" Structural I-Beam	• Lights - L.E.D. Stop, Tail, & Turn
• Tilt Deck - Custom Fabricated Beam w/ Lock	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 4" Channel w/ 16" Center	• Paint Prep - 3-Stage Clean-Up & Prime Coat
• Side Rails - 8" Channel w/ D-Rings	• Paint - Durable High Solids Acrylic Enamel
• Loading - Beveled Approach Plate w/ Recessed Lights & Tube Bumper	

Tilt Trailers

Standard Features	
• 5' Low Angle Dovetail	• Cushioning Tilt Cylinder
• Lockable Neck/Tongue Mounted Toolbox	
• Full-Length Diamond Plate Drive-Over Fenders	
• Lever Unlock/Self-Locking Tilt Deck Latch	

Optional Features	
• Floor, Brake & Axle Upgrades	• Maxx D-Ring Package
• 2-Speed Jack Upgrade	• Gooseneck Model (Dual Jacks)
• Power Tilt/Winch Plate (Deck Mnt.)	• Spare Mount (Ex. Gooseneck)
• Underbody Mounted 48" Steel Toolboxes	

Dimensions						
Weight/Length	A	B	C	D	E	Dove
7,000# - 25'	296"	150.5"	68"	34"	102"	60"
7,250# - 29'	340"	162.5"	68"	34"	102"	60"

