

10/12T Tagalong Workhorse Series

Pierced Frame


Tagalong Trailers

| Specifications | |
|--|---|
| • G.V.W.R. - 23,900# | • Axle - (2) 10,000# Oil-Bath Electric Brake |
| • G.A.W.R. (Each Axle) - 10,000# | • Suspension - 3" HD-Leaf Spring w/ Equalizer |
| • Coupler - Adjustable 3-Position Pintle Ring | • Tires - ST235/80R16 Load Range E |
| • Safety Chain - 3/8" Grade 43 w/ Hooks | • Wheel - Dually 16" 8-Bolt Grey (8 on 6.5 Pattern) |
| • Jack - Dual Bolt-On 10K Side Wind Drog Leg | • Deck - 2" Pressure Treated Pine |
| • Frame- 12" Structural I-Beam | • Lights - L.E.D. Stop, Tail, & Turn |
| • Frame Style - Pierced Frame Construction | • Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal |
| • Crossmembers - 3" Channel w/ 16" Centers | • Paint Prep - 3-Stage Clean-Up & Prime Coat |
| • Side Rails - 6" Channel w/ Rub Rail | • Paint - Durable High Solids Acrylic Enamel |
| • Ramps - 5' Heavy Duty Runner Style w/ Spring Assist & Lockable Ramp Bars | |

| Standard Features | |
|--|-------------------------|
| • 5' Self-Cleaning Dovetail | • Sealed Wiring Harness |
| • Lockable Tongue Mounted Toolbox | |
| • Full-Length Diamond Plate Drive-Over Fenders | |

| Optional Features | |
|-----------------------------------|-------------------------------|
| • Box End Tail or Pop-Up Dovetail | • Tie Down Options |
| • Diamond Plate Steel Floor | • 3rd Ramp/Headache Rack |
| • Jack, Axle & Brake Upgrades | • Spare Mount & Wheel Options |

| Dimensions | | | | | | |
|---|------|------|-----|-----|------|--------|
| Weight/Length | A | B | C | D | E | Dove |
| 5,700# - 20' | 240" | 142" | 68" | 34" | 102" | Boxend |
| 6,000# - 25' | 300" | 185" | 68" | 34" | 102" | 60" |
| 6,200# - 30' | 360" | 215" | 68" | 34" | 102" | 60" |
| 6,550# - 33' | 396" | 233" | 68" | 34" | 102" | 60" |
| 6,800# - 35'* | 420" | 245" | 68" | 34" | 102" | 60" |
| 7,300# - 40'* | 480" | 310" | 68" | 34" | 102" | 60" |
| ** 35' & 40' is custom built to order and require certain specifications sent in** | | | | | | |



D7

