

# 15T (Commercial) Tilt Series

## Fabricated-Deck

Specifications	
• G.V.W.R. - 32,500#	• Axle - (2) 15,000# Oil-Bath Electric Brake
• G.A.W.R. (Each Axle) - 15,000#	• Suspension - HD Hutch 9700-Style
• Coupler - 2-5/16" - Adjustable (Gooseneck/Pintle)	• Tires - ST215/75R17.5 Load Range H
• Safety Chain - 7/16" Grade 70 w/ Hooks	• Wheel - Dually 17.5" 8-Bolt Grey (8 on 275mm Pa.)
• Jack - Bolt-On 25K 2-Speed Landing Gear	• Deck - 2" Rough Cut Oak
• Frame- 14" Structural I-Beam	• Lights - L.E.D. Stop, Tail, & Turn
• Tilt Deck - Custom Fabricated Beam w/ Lock	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 4" Channel w/ 16" Center	• Paint Prep - 3-Stage Clean-Up & Prime Coat
• Side Rails - 8" Channel w/ (10 Total) D-Rings	• Paint - Durable High Solids Acrylic Enamel
• Loading - Beveled Approach Plate w/ Recessed Lights & Tube Bumper	

Tilt Trailers

Standard Features	
• 5' Low Angle Dovetail	• Cushioning Tilt Cylinder
• Lockable Neck/Tongue Mounted Toolbox	
• Full-Length Diamond Plate Drive-Over Fenders	
• Lever Unlock/Self-Locking Tilt Deck Latch	

Optional Features	
• Spare Mount/Steel Floor Upgrade	• Maxx D-Ring Package
• Air Brake Upgrade	• Gooseneck Model (Dual Jacks)

Dimensions						
Weight/Length	A	B	C	D	E	Dove
7,000# - 25'	296"	150"	68"	34"	102"	60"
7,200# - 29'	340"	162"	68"	34"	102"	60"

