

# 5/6/7T (Commercial) Tilt Series

5T Specifications	
• G.V.W.R. - 9,950#	• Axle - (2) 5,200# Torsion Electric Brake
• G.A.W.R. (Each Axle) - 5,200#	• Suspension - Torsion Arm Type
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST225/75R15 Load Range D
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 15" 6-Bolt White Spoke (6 on 5.5 Pattern)
• Jack - Bolt-On 7K Top Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Tongue - 6" Channel	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 6" Channel	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x72" - Diamond Plate w/ Steel Steps	• Paint - Super Durable Powdercoat
• Loading - Beveled Approach Plate w/ Recessed Lights & CNC'd Tube Bumper	

Tilt Trailers

6T Specifications
• G.V.W.R. - 12,000#
• G.A.W.R. (Each Axle) - 6,000#
• Axle - (2) 6,000# Torsion Electric Brake
• Tires - ST235/80R16 Load Range E
• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)

7T Specifications
• G.V.W.R. - 14,000#
• G.A.W.R. (Each Axle) - 7,000#
• Axle - (2) 7,000# Torsion Electric Brake
• Tires - ST235/80R16 Load Range E
• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)

Optional Features	
• Wheel & Surge Brake Upgrade	• Tie Down & Floor Options

Dimensions					
Weight/Length	A	B	C	D	E
3,200# - 14'	192"	112"	46"	24"	79"
3,300# - 16'	216"	124"	46"	24"	79"
3,400# - 18'	240"	136"	46"	24"	79"

