

5/6K (Single Axle) Tilt Series

Specifications	
• G.V.W.R. - 5,200#	• Axle - (1) 5,200# Cambered Electric Brake
• G.A.W.R. (Each Axle) - 5,200#	• Suspension - Multi-Leaf Slipper Spring
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST225/75R15 Load Range D
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 15" 6-Bolt White Spoke (6 on 5.5 Pattern)
• Jack - Bolt-On 7K Top Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Tongue - 6" Channel	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 6" Channel	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x36" - Diamond Plate w/ Steel Steps	• Paint - Super Durable Powdercoat
• Loading - Beveled Approach Plate w/ Recessed Lights & CNC'd Tube Bumper	

Tilt Trailers

Optional Features	
• Wheel & Surge Brake Upgrade	• Tie Down Packages
• 6K Axle Upgrade	• Diamond Plate Steel Floor

Dimensions					
Weight/Length	A	B	C	D	E
2,750# - 12'	144"	85"	44"	20"	76"

