

7T (Commercial) Partial-Tilt Series

Specifications	
• G.V.W.R. - 14,000#	• Axle - (2) 7,000# Torsion Electric Brake
• G.A.W.R. (Each Axle) - 7,000#	• Suspension - Torsion Arm Type
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST235/80R16 Load Range E
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)
• Jack - Bolt-On 7K Top Wind Droq Leg	• Deck - 2" Pressure Treated Pine
• Tongue - 2x6" Tube	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 6" Channel	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 4" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x72" - Diamond Plate w/ Steel Steps	• Paint - Super Durable Powdercoat
• Loading - Beveled Approach Plate w/ Recessed Lights & CNC'd Tube Bumper	
• Stationary Front Deck - 48" Length w/ Side Locking Tilt Deck Latch	

Tilt Trailers

Optional Features	
• Steel Floor Upgrade	• Tie Down Packages
• Surge Brake Upgrade	• Gooseneck Model
• Spare Mount & Wheel Options	

Dimensions							
Weight/Length	A	B	C	D	E	F	G
3,350# - 18'	216"	124"	48"	25"	79"	48"	168"
3,450# - 20'	240"	136"	48"	25"	79"	48"	192"

