

7T Gooseneck Workhorse Series

Pierced Frame


Gooseneck Trailers

Specifications	
• G.V.W.R. - 14,000#	• Axle - (2) 7,000# Cambered Electric Brake
• G.A.W.R. (Each Axle) - 7,000#	• Suspension - Multi-Leaf Spring w/ Equalizer
• Coupler - 2-5/16" - Adjustable Gooseneck	• Tires - ST235/80R16 Load Range E
• Safety Chain - 3/8" Grade 53 w/ Hooks	• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)
• Jack - Dual Bolt-On 10K Side Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Frame- 12" Structural I-Beam	• Lights - L.E.D. Stop, Tail, & Turn
• Frame Style - Pierced Frame Construction	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3" Channel w/ 16" Centers	• Paint Prep - 3-Stage Clean-Up & Prime Coat
• Side Rails - 6" Channel w/ Rub Rail	• Paint - Durable High Solids Acrylic Enamel
• Ramps - 5' Heavy Duty Runner Style w/ Spring Assist & Lockable Ramp Bars	

Standard Features	
• 5' Self-Cleaning Dovetail	• Spare Tire Mount in Neck
• Lockable Neck Mounted Toolbox w/ Gas Shocks	
• Full-Length Diamond Plate Drive-Over Fenders	

Optional Features	
• Box End Tail or Pop-Up Dovetail	• Tie Down Options
• Deck Over Neck/Steel Floor	• 3rd Ramp/Headache Rack
• Jack, Axle & Brake Upgrades	• Spare Mount & Wheel Options

Dimensions						
Weight/Length	A	B	C	D	E	Dove
5,550# - 20'	240"	142"	98"	35"	102"	Boxend
5,750# - 25'	300"	183"	98"	35"	102"	60"
5,950# - 30'	360"	215"	98"	35"	102"	60"



C1