

8T (Commercial) Partial-Tilt Series

Specifications	
• G.V.W.R. - 16,000#	• Axle - (2) 8,000# Torsion Electric Brake
• G.A.W.R. (Each Axle) - 8,000#	• Suspension - Torsion Arm Type
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST215/75R17.5 Load Range E
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 17.5" 8-Bolt Grey Spoke (8 on 6.5 Pattern)
• Jack - Bolt-On 10K Side Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Tongue - 3x8" Tube	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 3x8" Tube	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 4" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x72" - Diamond Plate w/ Steel Steps	• Paint - Super Durable Powdercoat
<ul style="list-style-type: none"> • Loading - Beveled Approach Plate w/ Recessed Lights & CNC'd Tube Bumper • Stationary Front Deck - 48" Length w/ Side Locking Tilt Deck Latch 	

Tilt Trailers

Optional Features	
• Steel Floor Upgrade	• Maxx D-Ring Package
• Side Fork Holder	• Gooseneck Model
• Bolt-On Spare Tire Mount	

Dimensions							
Weight/Length	A	B	C	D	E	F	G
4,200# - 20'	240"	136"	48"	26"	78"	48"	192"
4,300# - 22'	264"	148"	48"	26"	78"	48"	216"

