

# EC (Economy) Utility Series

| Specifications  |   |
|---|---|
| • G.V.W.R. - 1,900#   | • Axle - (1) 2,000# Straight EZ-Lube Idler          |
| • G.A.W.R. (Each Axle) - 2,000#   | • Suspension - Multi-Leaf Slipper Spring            |
| • Coupler - 2" - Straight Type  | • Tires - ST175/80R13 Load Range B                  |
| • Safety Chain - 3/16" Grade 41 w/ Hooks  | • Wheel - 13" 5-Bolt White Spoke (5 on 4.5 Pattern) |
| • Tongue - 2x3" 11Ga. Tube  | • Deck - Expanded Metal                             |
| • Frame - 3x2x3/16" Angle   | • Lights - L.E.D. Stop, Tail, & Turn                |
| • Crossmembers - 3x2x3/16" Angle w/ 24" Centers   | • Vehicle Plug - 4-Way Flat w/ SnapNSeal Harness    |
| • Top Rail - 2x2x1/8" Angle   | • Paint Prep - 5-Stage Super Blast Treatment        |
| • Uprights - 2x2x1/8" Angle   | • Paint - Super Durable Powdercoat                  |
| • Fenders - 9x32" - Flat Top Jeep Style   | • Gate - 3' Swing-Down w/ Drop-In L-Pin Style       |
| * 6' Wide Models Only Include - 2" A-Frame Style Coupler, 3x2x1/8" Angle Tongue, & 2K Top Wind Jack * |   |

| Optional Features  |
|--------------------|
| • Wood Floor       |
| • 3K Swing-Up Jack |

| Dimensions    |      |     |     |     |     |
|---------------|------|-----|-----|-----|-----|
| Weight/Length | A    | B   | C   | D   | E   |
| 470# - 4x8'   | 98"  | 60" | 36" | 16" | 50" |
| 490# - 5x8'   | 98"  | 60" | 36" | 16" | 60" |
| 525# - 5x10'  | 122" | 72" | 36" | 16" | 60" |
| 545# - 6x10'  | 122" | 72" | 36" | 16" | 72" |

