

# LST (Landscape Tandem) Utility Series

| Specifications   |   |
|--|---|
| • G.V.W.R. - 7,000#  | • Axle - (2) 3,500# Cambered Electric Brake         |
| • G.A.W.R. (Each Axle) - 3,500#  | • Suspension - Multi-Leaf Spring w/ Equalizer       |
| • Coupler - 2" - Adjustable Bolt-On  | • Tires - ST205/75R15 Load Range C                  |
| • Safety Chain - 8/0 Grade 41 w/ Hooks   | • Wheel - 15" 5-Bolt White Spoke (5 on 4.5 Pattern) |
| • Jack - 2K Top-Wind Pole  | • Deck - 2" Pressure Treated Pine                   |
| • Tongue - 4x3x1/4" Angle  | • Lights - L.E.D. Stop, Tail, & Turn                |
| • Frame - 3x2x3/16" Angle (3x4x1/4" Angle-18'+)  | • Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal  |
| • Crossmembers - 3x2x3/16" Angle w/ 24" Centers  | • Paint Prep - 5-Stage Super Blast Treatment        |
| • Top Rail - 2x2" 14Ga.(2x3" 11Ga. Tube-18'+)  | • Paint - Super Durable Powdercoat                  |
| • Uprights - 2x2x1/8" Angle w/ Spare Mount   | • Gate - 4' Swing-Down w/ CNC Machined Pins         |
| • Fenders - 9x72" - Diamond Plate w/ Steel Backs   | • Gate Lock - CNC Machined Lockable Pin Latch       |
| *Bumper - 2x4" 14Ga. CNC Laser Tubed w/ Concealed Tag Mount & Integrated EZ-Shock Gate Assist* |   |

| Optional Features             |                          |
|-------------------------------|--------------------------|
| • Tie Down Packages           | • Multiple Wheel Options |
| • Higher & Covered Side Rails | • Jack Upgrades          |
| • Bolt-On Coupler Upgrades    | • Brake Axle Upgrades    |

| Dimensions   |      |       |       |     |     |
|--|------|-------|-------|-----|-----|
| Weight/Length  | A    | B     | C     | D   | E   |
| 1,290# - 10'   | 120" | 81.5" | 38.5" | 20" | 76" |
| 1,380# - 12'   | 144" | 93"   | 38.5" | 20" | 76" |
| 1,470# - 14'   | 168" | 104"  | 38.5" | 20" | 76" |
| 1,560# - 16'   | 192" | 114"  | 38.5" | 20" | 76" |
| 1,650# - 18'   | 216" | 124"  | 38.5" | 20" | 76" |
| 1,740# - 20'   | 240" | 134"  | 38.5" | 20" | 76" |
| 1,830# - 22'   | 264" | 144"  | 38.5" | 20" | 76" |
| * 7' Wide Models Only - E=82" & 75-150# Added to 6' Wide Models* |      |       |       |     |     |

