

PEQ (Pipe Top Rail) Equipment Series

Equipment Trailers

Specifications	
• G.V.W.R. - 12,000#	• Axle - (2) 6,000# Cambered Electric Brake
• G.A.W.R. (Each Axle) - 6,000#	• Suspension - Multi-Leaf Spring w/ Equalizer
• Coupler - 2-5/16" - Adjustable Type	• Tires - ST235/80R16 Load Range E
• Safety Chain - 3/8" Grade 43 w/ Hooks	• Wheel - 16" 8-Bolt White Spoke (8 on 6.5 Pattern)
• Jack - Bolt-On 10K Side Wind Drog Leg	• Deck - 2" Pressure Treated Pine
• Tongue - Wrapped 6" Channel	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 5" Angle w/ 2-1/2" Pipe Top Rail	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3" Channel w/ 16" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Fenders - 9x72" - Diamond Plate w/ Steps	• Paint - Super Durable Powdercoat
• Ramps - 5' Runner Style Fold Down w/ Spring Assist & Lockable Ramp Bars	

Optional Features	
• Side & Floor Options	• Tie Down Packages
• 5' Double Split Gates w/ Assist	• Deck & Gooseneck Options
• Coupler, Axle, & Brake Upgrades	• Spare Mount & Wheel Options

Dimensions					
Weight/Length	A	B	C	D	E
3,200# - 12'	144"	95.5"	43"	25.5"	82"
3,350# - 14'	168"	107.5"	43"	25.5"	82"
3,500# - 16'	192"	119.5"	43"	25.5"	82"
3,650# - 18'	216"	131.5"	43"	25.5"	82"
3,800# - 20'	240"	143.5"	43"	25.5"	82"
3,950# - 22'	264"	155.5"	43"	25.5"	82"
4,000# - 24'	288"	167.5"	43"	25.5"	82"

