

SB (Solid Side Rental) Utility Series

Specifications	
• G.V.W.R. - 2,900#	• Axle - (1) 3,500# 4" Drop EZ-Lube Idler
• G.A.W.R. (Each Axle) - 3,500#	• Suspension - Multi-Leaf Double-Eye Spring
• Coupler - 2" - Adjustable Bolt-On	• Tires - ST205/75R15 Load Range C
• Safety Chain - 3/16" Grade 30 w/ Hooks	• Wheel - 15" 5-Bolt White Spoke (5 on 4.5 Pattern)
• Jack - 2K Removeable Swing-Up	• Deck - 2" Pressure Treated Pine w/ D-Rings
• Tongue - 4x3x1/4" Angle	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 3x2x3/16" Angle	• Vehicle Plug - 4-Way Flat w/ SnapNSeal Harness
• Crossmembers - 3x2x3/16" Angle w/ 24" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Top Rail - 2x2" 11 Ga. Tube w/ Spare Mount	• Paint - Super Durable Powdercoat
• Sides - 2x2" 11 Ga. Tube w/ 2' V-Panels	• Gate - 4' HD-X Rental Style w/ Angle Runners
• Fenders - 9x32" - Roll Formed w/ Steel Backs	• Gate Lock - Bolt-On Drop-In L-Pins
Bumper - 2x4" 14Ga. CNC Laser Tubed w/ Winged Light Brace & Tag Mount	

Optional Features
• Idler, Surge, & Electric Brake Axle Upgrades

Dimensions					
Weight/Length	A	B	C	D	E
990# - 4x8'	96"	84"	21.5"	20"	50"
1,140# - 5x8'	96"	84"	21.5"	20"	60"
1,160# - 5x10'	120"	69.5"	21.5"	20"	76"
1,225# - 6x8'	96"	84"	21.5"	20"	76"
1,250# - 6x10'	120"	69.5"	21.5"	20"	76"

