

UTT-HD Utility Series

(Utility Tractor Tandem Heavy Duty)

Specifications	
• G.V.W.R. - 9,950#	• Axle - (2) 5,200# Cambered Electric Brake
• G.A.W.R. (Each Axle) - 5,200#	• Suspension - Multi-Leaf Spring w/ Equalizer
• Coupler - 2-5/16" Adjustable Bolt-On	• Tires - ST225/75R15 Load Range D
• Safety Chain - 8/0 Grade 30 w/ Hooks	• Wheel - 15" 6-Bolt White Spoke (6 on 5.5 Pattern)
• Jack - 7K Drop Leg Bolt-On	• Deck - 2" Pressure Treated Pine
• Tongue - 5" Channel Wrapped	• Lights - L.E.D. Stop, Tail, & Turn
• Frame - 4x3x1/4" Angle	• Vehicle Plug - 7-Way RV w/ Breakaway & SnapNSeal
• Crossmembers - 3x2x3/16" Angle w/ 24" Centers	• Paint Prep - 5-Stage Super Blast Treatment
• Top Rail - 2x3" 11Ga. Tube w/ Spare Mount	• Paint - Super Durable Powdercoat
• Uprights - 2x2x1/8" Angle	• Gate Standard - 2" Rear Board Stop Track
• Fenders - 9x72" - Diamond Plate w/ Steel Backs	• Loading Standard - 5' Slide-In (Store Under Rear)
Bumper - 2x4" 14Ga. CNC Laser Tubed w/ Concealed Tag Mount & Loading Track	

Optional Features	
• Tie Down Packages	• Multiple Wheel Options
• Higher & Covered Side Rails	• 5' EQ-Style Ramps
• Side Fender Steps	• Surge Brake Upgrade

Dimensions					
Weight/Length	A	B	C	D	E
1,600# - 14'	168"	104"	38.5"	20"	76"
1,700# - 16'	192"	114"	38.5"	20"	76"
1,800# - 18'	216"	124"	38.5"	20"	76"
1,900# - 20'	240"	134"	38.5"	20"	76"
* 7' Wide Models Only - E=82" & 75-150# Added to 6' Wide Models*					

